

Product Specification:	Document No	PS-HRS-9502-01
Subject: 9.50mm Pitch HRS-9502Series Connector Specification	Date Issued	2016/07/20
	Date Revised	2020/05/19
	Version	B

This specification is referred to the 9.50mm series wire to board connector

INDEX


1. Scope
2. Spec and Part number
3. Disposal of Material and surface
4. Ratings and applicable wires
5. Performance
 - 5-1. Electrical Performance.
 - 5-2. Mechanical Performance
 - 5-3.Environmental Performance and Others

Product Specification:	Document No	PS-HRS-9502-01
Subject: 9.50mm Pitch HRS-9502Series Connector Specification	Date Issued	2016/07/20
	Date Revised	2020/05/19
	Version	B

1. Scope

This Specification Covers the 9.50mm Pitch HRS-9502 Series Connector Specification.

2. Spec and Part number

Specification	Production No.	Picture of Product
Terminal Blocks	HRS-9502WV-XX-N0SWBK	

3. Disposal of Material and surface

Specification	Materials	Disposal of Surface
Terminal Blocks	Housing	PA66
	Terminal	UL94V-0
	Screw	3-5μm Sn Over 1-2μm Cu
	Steel	2-5μm Zn

(Please Refer to the Project drawing for the above Specification)

4. Ratings and applicable wires

Item	Standard	
Rated Voltage (Max.)	300V	[AC/DC]
Rated Current (Max.)	30A	
Ambient temperature Range	-40℃~105℃	
Applicable wire insulation O.D	AWG #12~22	

*Including terminal temperature rise.

Product Specification:	Document No	PS-HRS-9502-01
Subject: 9.50mm Pitch HRS-9502Series Connector Specification	Date Issued	2016/07/20
	Date Revised	2020/05/19
	Version	B

5. PERFORMANCE

5-1. Electrical Performance.

Item		Test Condition	Requirement
5-1-1	Contact Resistance	Mate connectors, measure by dry circuit, 20mV MAX,10mA. (Based upon EIA-364-06A).	Initial: 30 milliohms Max.
5-1-2	Insulation Resistance	Mate connectors, apply 1000V DC between adjacent terminal or ground. (Based upon EIA-364-21B / MIL-STD-202 Method 302 Cond.B)	1000 Megohms Min.
5-1-3	Dielectric Strength	Mate connectors, apply 3400V AC for 1 minute between adjacent terminal or ground. (Based upon EIA-364-20A / MIL-STD-202 Method 301)	No Breakdown and Flashover

5-2. Mechanical Performance.

Item		Test Condition	Requirement
5-2-1	Terminal Retention	Force required to dislodge terminals from the housing, applied at a rate of 25 ± 6 mm ($1 \pm \frac{1}{4}$ inch) per minute, in the direction opposite terminal insertion.	150N {15.3kgf} min.
5-2-2	Screw Torque	Tighten screw to 110% rated torque [1.01 Nm(9.0 in-lb)] with max. and min. wire sizes and loosen 5 times per	No damage to housing, terminal, or screw

5-3. Environmental Performance and Others.

Item		Test Condition	Requirement	
5-3-1	Temperature Rise	Carrying rated current load.	Temperature rise	30°C Max.
5-3-2	Salt Spray	24±1 hours exposure to a salt spray from the 5±1% solution at 35±2°C. (Based upon EIA-364-26A/MIL-STD-202 Method 101D Cond.B).	Appearance	No Damage